

WeatherStation® Multisensors

A Compact, Rugged Instrument for Informed Decision-Making



Ultrasonic Instruments

Rugged Reliability,
Proven Performance.

The Airmar WeatherStation Instruments are unique, as they are the only weather monitoring system that can report Dynamic True and Apparent wind speed and direction/angle in one compact housing with no moving parts or external interfaces.



Ultrasonic Wind Measurement
Dynamic True and Apparent wind speed and direction with no moving parts



Relative Humidity (optional)
Field serviceable RH sensor with calculated dew point



Rain Measurement
Maintenance free acoustic rain measurement including duration, intensity and amount with 95% accuracy



Barometric Pressure
Accurate atmospheric pressure measurement



10 Hz GPS
Position, COG, SOG, time stamping



Solar Stabilization
Solar radiation shield increases the accuracy and stability of temperature and relative humidity readings



Air Temperature
With calculated heat index and wind chill when RH module is installed



3-Axis Compass
With dynamic stabilization and better than 1° accuracy



3-Axis Rate Gyro
For rate-of-turn data



3-Axis Accelerometer
For pitch and roll



	110WX	200WX	200WX-IPX7	220WXH	150WXS	150WXS
Apparent wind speed and angle	✓	✓	✓	✓	✓	✓
Dynamic True wind speed and direction		✓	✓	✓	✓	✓
Barometric pressure	✓	✓	✓	✓	✓	✓
Air temperature	✓	✓	✓	✓	✓	✓
10 Hz GPS (Position, COG, SOG)		✓	✓	✓	✓	✓
Three-axis accelerometer for pitch & roll		✓	✓	✓	✓	✓
Two-axis solid-state compass: Better than 1° static compass accuracy					✓	
Three-axis solid-state compass with dynamic stabilization: Better than 1° static compass accuracy Best-in-class 2° dynamic compass accuracy		✓	✓	✓		✓
Three-axis rate gyros provide rate-of-turn data		✓	✓	✓		✓
Solar shield					✓	✓
Rain accumulation, duration, intensity						✓
Heater				✓		
Relative humidity (field-serviceable)	✓	✓			✓	✓
Calculated dew point	Optional	Optional			Standard	Standard
Calculated heat index						
Weatherproof rating	IPX6*	IPX6*	IPX7	IPX6	IPX4	IPX4
Operating voltage	9-40 VDC	9-40 VDC	9-40 VDC	12-24 VDC	9-40 VDC	9-40 VDC
Output options include:	✓	✓	✓	✓	✓	✓
Hardware Interfaces: Serial RS232, Serial RS422, CAN				(0183 only)		
Protocols: NMEA 0183, NMEA 2000®						
Serial Data Transmission Code: ASCII						

* Rating stated is without optional RH sensor installed.



WEATHERSTATIONWX.COM



©2024 AIRMAR Technology Corporation

WXSERIES_SHEET_rc 04/11/24

As AIRMAR constantly improves its products, all specifications are subject to change without notice. All AIRMAR products are designed to provide high levels of accuracy and reliability, however they should only be used as aids to navigation and not as a replacement for traditional navigation aids and techniques. WeatherStation® and are registered trademarks and trademarks of AIRMAR Technology Corporation. AMPHENOL is a registered trademark of Amphenol Corporation. Other company or product names mentioned in this document may be trademarks or registered trademarks of their respective companies, which are not affiliated with AIRMAR.